

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 31 EAST, MDM, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by G.W. Garside and C.S. Preble, U.S. Deputy Surveyors, in 1875.</p>
	<p>The standard cor. of secs. 32 and 33, monumented with a trapstone, 20x12x10, firmly set and exposed 12 ins. above the ground, plainly mkd. with 4 grooves on E. face, 2 grooves W. face and 6 grooves on N. face. This cor. now refers to the SE. cor. of sec. 32, only.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground over a DEEP-1 magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">SC T46N R31E <u>S 32</u> 1991</p>
	<p>Deposit the original cornerstone and set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the stainless steel post.</p>
	<p>From this corner, the standard cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey in T. 46 N., R. 31 E., executed under Group No. 88, bears N. 47°37' E., 2.04 chs. dist. This cor. now refers to the SW. cor. of sec. 33, only. Remark the brass cap to read as follows:</p>
	<p style="text-align: center;">SC T46N R31E <u>S 33</u> 1923 1991</p>
	<p>N. 88°32' W., along the S. bdy. of sec. 32.</p>
	<p>Over rolling land, through scattered sagebrush and native grass.</p>
2.00	Sage Hen Creek, dry channel, 10 lks. wide, 2 ft. deep, course SW.
39.00	Little Sage Hen Creek, dry channel, 10 lks wide, 2 ft. deep, course SSW.
40.10	Fence, bears N. and S.
42.45	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground over a DEEP-1 magnetic marker, with brass cap mkd.</p>