## DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 31 EAST, MDM, NEVADA

CHAINS	sc
	T46N R31E 1/4 S 32
	1991
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
84.90	Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground over a DEEP-1 magnetic marker, with brass cap mkd.
	SC T46N R31E S 31 S 32
	1991
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
	N. 88°32' W., along the S. bdy. of sec. 31.
	Over rolling land, through scattered sagebrush and native grass.
25.60	Trail road, bears NW. and SE.
27.20	Wash, 10 lks. wide, 1 ft. deep, drains SE.
42.45	Point for the standard $^{1}/_{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground over a DEEP-1 magnetic marker, with brass cap mkd.
	SC T46N R31E 1/4 S 31
	1991
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
69.32	The closing cor. of Tps. 45 N., Rs. 30 and 31 E., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey in T. 45 N., R. 30 E., executed concurrently under this same Group.