CHAINS	
	DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by W.H. Myrick, U. S. Deputy Surveyor, in 1882, and a Portion of the Dependent Resurvey Executed by
	C.S. Swanholm, Cadastral Engineer in 1930-1933
	From the true point for the cor. of secs. 19, 24, 25 and 30. N. 0°04.4' E., bet. secs. 19 and 24.
	Over mountainous land, through scattered creosote brush and Brigham tea.
0.540	The witness cor. of secs. 19, 24, 25 and 30, monumented with ar iron post, 2 ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 18 S., R. 63 E., executed under Group No. 159. Add the marks 1992 to the cap.
	N 0004 4/ E boginning new management
	N. 0°04.4' E., beginning new measurement.
39.058	The witness ¹ / ₄ sec. cor. of secs. 19 and 24, monumented with ar iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S.,
39.058	The witness ¹ / ₄ sec. cor. of secs. 19 and 24, monumented with ar iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S., R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E
39.058	The witness ¹ / ₄ sec. cor. of secs. 19 and 24, monumented with ar iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S., R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E
39.058	The witness ¹ / ₄ sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S. R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E 1/4 WC
39.058	The witness \$\frac{1}{4}\$ sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S. R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E 1/4 WC \$ 24 \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$
0.400	The witness \$\frac{1}{4}\$ sec. cor. of secs. 19 and 24, monumented with ar iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S., R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E 1/4 WC S 24 S19 1992 1933 N. 0°04.4' E., beginning new measurement.
	The witness \$\frac{1}{4}\$ sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 18 S., R. 63 E., executed under Group No. 159. Remark the cap to read as follows: T18S R63E R64E 1/4 WC 5 24 \$19 1992 1933 N. 0°04.4' E., beginning new measurement. True point for the \$\frac{1}{4}\$ sec. cor. of secs. 19 and 24, at