DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 18 S., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 18 S., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by W.H. Myrick, U. S. Deputy Surveyor, in 1882,

and a Portion of the Dependent Resurvey Executed by C.S. Swanholm, Cadastral Engineer, in 1930-1933.

From the cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set in a concrete cylinder, 18 ins. diam., exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the concurrent dependent resurvey by Robert A. Pratt, Cadastral Surveyor, under Group 732, Nevada.

From this corner, U.S.C. & G.S. triangulation station "GARNET" monumented with a standard brass tablet stamped GARNET 1957, cemented in a drill hole in an outcropping of bedrock, bears S. 41°09.2' E., 5.012 chs. dist.

N. 0°04.1' E. bet. secs. 7 and 12.


Over rolling land, through scattered creosote brush and Brigham tea.

0.738

Intersect easterly right-of-way Interstate Highway No. 15, bears N. 26°28.7′ E. and S. 26°28.7′ W.

Point for a witness point on line bet. secs. 7 and 12.

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 14 ins. in the ground to solid rock over a DEEP-1 magnetic marker, with brass cap mkd.



1992

From this witness point, a Nevada Highway Department station, monumented with a standard brass tablet, firmly set in a concrete post, 18 ins. diam., with tablet mkd. E 1121+84.48 DIST. 54.24 ANGLE 90, bears N. 25°15.8' E., 104.098 chs. dist.

From this same witness point, a Nevada Highway Department station, monumented with a standard brass tablet, firmly set in a concrete post, 12 ins. diam., with tablet mkd. E 1023 +11.35 POT DIST. 52.27 ANGLE 90, bears S. 29°17.6′ W., 45.569 chs. dist.