

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 57 EAST, M.D.M., NEVADA

CHAINS

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 57 EAST, M.D.M., NEVADA

Reestablishment of the Survey Executed by J. M. Brunt
and W. H. Proctor, U. S. Deputy Surveyors,
in 1881

From the standard cor. of secs. 31 and 32, monumented with the remains of a wooden post, 3 ins. square, 6 ins. long, firmly set in a mound of stone, with illegible scribing visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground, over a DEEP-1 magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

SC
T20S R57E
S 31 | S 32

1993

Deposit the remains of the original wooden post and set a U shaped aluminum post, 6 ft. long, alongside the stainless steel post.

S. 88°56.0' W., on the S. bdy. of sec. 31.

Over mountainous land, covered with scattered sagebrush, cacti, Brigham tea, native grass, manzanita, scrub oak, juniper and pinion pine.

19.918 Point for the standard E $\frac{1}{16}$ sec. cor. of sec. 31.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, over a DEEP-1 magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

SC
T20S R57E
E $\frac{1}{16}$ S 31

1993

Set a U shaped aluminum post, 6 ft. long, alongside the stainless steel post.

39.836 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

SC
T20S R57E
 $\frac{1}{4}$ S 31

1993