DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 5 S., R. 60 E., MDM, NEVADA

CHAINS Reestablishment of the Survey Executed by E. B. Monroe, U. S. Deputy Surveyor in 1870 From the cor. of secs. 25, 26, 35 and 36, monumented with a juniper post, 3 ins. square, 4 ft. long, mkd. SXXV on the E. face, TVS RLXE SXXVI on the N. face and illegible scribes on the S. and W. faces, firmly set in a mound of stone. At the corner point Set a stainless steel post, 28 ins. long,  $2^{1}/_{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd. **T5S R60E** S 26 S 25 S 35 S 36 1990 Reset the original wooden post and set a steel fence post,  $5^{1}/_{2}$  ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. From this corner, U.S.G.S. triangulation station "ASH ET", monumented with a standard brass tablet stamped ASH ET 1969 on copperweld rod, bears S. 37°54' E. (mean bearing), 156.17 chs. dist. N. 0°34.4' W., bet. secs. 25 and 26. Over nearly level land, through meadow grass. Fence, bears NNW. and SSE. 11.60 15.20 Fence, bears E. and W. 18.30 Fence, bears E. and W. Brownie Spring, bears W., 1.30 chs. dist. 21.35 Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate 39.768 distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long,  $2^{1}/_{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd. **T5S R60E** s 26 | s 25 1990