55

SUBDIVISION OF SECTION 26,
T. 5 S., R. 60 E., MDM, NEVADA

CHAINS	
	From the $1/4$ sec. cor. of secs. 26 and 35.
	N. 0°35.5' W., on the N-S center line of sec. 26.
40.016	Point for the center $1/4$ sec. cor. of sec. 26, at intersection with the E-W center line of sec. 26.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

<div align="center">

T5S R60E
C $1/4$ S 26

1990

</div>

	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
60.026	Point for the C-N $1/_{16}$ sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

<div align="center">

C
N $1/_{16}$ | S 26
C

1990

</div>

	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
80.036	The $1/4$ sec. cor. of secs. 23 and 26.

	From the $1/4$ sec. cor. of secs. 25 and 26.
	N. 89°34.8' W., on the E-W center line of sec. 26.
2.20	Fence, bears NNW. and SSE.
2.60	Dirt road, bears NNW. and SSE.
20.073	Point for the C-E $1/_{16}$ sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

<div align="center">

E $1/_{16}$
C ——————— C
S 26

1990

</div>

	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
40.146	The center $1/4$ sec. cor. of sec. 26.