DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 42 N., R. 22 E., MDM, NEVADA

	· · · · · · · · · · · · · · · · · · ·
CHAINS	
41.93	Point for the 1 / $_{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T43N R22E S 31
	1/4 ——
	S 6 T42N
	1989
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
82.53	The cor. of Tps. 42 and 43 N., Rs. 21 and 22 E., monumented with an iron post, $2^{1}/_{2}$ ins. diam., firmly set exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 42 N., R. 21 E., executed under Group No. 459.
	DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 42 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by G. W. Garside and C. S. Preble, U.S. Deputy Surveyors, in 1875 and 1877.
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
	N. 4° 04' W., bet. secs. 35 and 36.
	Over rolling land, through scattered sagebrush and native grass.
10.30	Trail road, bears WNW. and ESE.
41.54	Point for the $^{1}/_{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T42N R22E
	s 35 s 36
	1989
83.08	The cor. of secs. 25, 26, 35 and 36, monumented with a trapstone, 34x18x6 ins., plainly mkd. with 1 notch on the S. and E. edges, firmly set in a mound of stone.