

144

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T19S R61E R62E S 1 S 6 <hr style="width: 50%; margin: auto;"/>S 12 S 7 1991</p> <p>Insert the iron rebar inside the stainless steel post.</p> <p>From this corner, an iron rebar, $\frac{1}{2}$ in. diam., firmly set flush with the ground, with a yellow plastic cap, mkd. "RLS 4024," bears N. $4^{\circ}02'$ W., 2.327 chs. dist.</p> <hr/> <p>N. $0^{\circ}15.8'$ E., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with scattered creosote brush, yuccas and cacti.</p> <p>2.00 Trail road, bears on curve NNW. and S.</p> <p>12.00 Trail road, bears on curve SSW. and N.</p> <p>36.50 Trail road, bears on curve NNW. and S.</p> <p>40.977 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with an iron rebar, $\frac{1}{2}$ in. diam., 18 ins. long, firmly set showing 3 ins. above the ground, with yellow plastic cap mkd. "RLS 4024", and a sandstone 12x7x3 ins., plainly mkd. $\frac{1}{4}$ on W. face, lying alongside. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19S R61E R62E $\frac{1}{4}$ S 1 S 6 1991</p> <p>Insert the iron rebar inside the stainless steel post and deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, an iron rebar, $\frac{1}{2}$ in. diam., firmly set showing 3 ins. above the ground, with a yellow plastic cap, mkd. "RLS 4024," bears S. $49^{\circ}46'$ E., 0.974 chs. dist.</p> <hr/> <p>N. $0^{\circ}02.0'$ W., beginning new measurement.</p> <p>Over rolling land.</p> <p>5.40 Trail road, bears on curve SSW. and N.</p>