SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 4 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 4 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Point for the W $^{1}/_{4}$ sec. cor. of sec. 19, is on the E. bdy. of sec. 24, T. 4 N., R. 51 E. and at midpoint bet. the closing corners.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4N ¹ / ₄ S 19 R52E
	1990
	Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	From this corner the cor. of secs. 13 and 24, T. 4 N., R. 51 E., bears N. 0°06' E., 4.735 chs. dist., hereinbefore described.
	SUBDIVISION OF SECTION 19, T. 4 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.
	N. 0°04' W., on the N. and S. center line of sec. 19.
15.50	Center of State Highway No. 375, 30 lks. wide, bears NW. and SE.
20.00	Point for the C-S 1 / $_{16}$ sec. cor. of sec. 19.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	s ¹ / ₁₆ s 19 C
	1990
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cor. is located on sagebrush flat.
29.60	Trail road, bears SE. and NW.
33.80	Center of County access road, to Twin Springs, 25 lks. wide, bears SW. and NE.
36.30	Twin Springs Slough, 15 lks. wide, 2 ft. deep, course E.
39.70	Center of County access road, to Twin Springs, 35 lks. wide, bears NW. and SE.
40.00	Point for the center $^{1}/_{4}$ sec. cor. of sec. 19, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.