

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Reestablishment of a Portion of the Survey Executed by A. J. Hatch, J. H. Eaton and J. C. Smyles, U.S. Deputy Surveyors in 1872, and a Portion of the Resurvey Executed by R. A. Pratt and R. E. Williams, Cadastral Surveyors, in 1987 From the cor. of secs. 27, 28, 33 and 34, monumented with a stainless steel post, 2½ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 30 N., R. 56 E., executed under Group No. 648. Add the marks 1992 to the cap. N. 0°42' W., bet. secs. 27 and 28. Over rolling land, through scattered sagebrush, rabbitbrush and native grass.
19.888	Point for the S 1/16 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd. S 1/16 S 28 S 27 1992
21.10	Trail road, bears E. and W.
21.40	Trail road, bears WNW. and ESE.
23.60	Fence, bears ENE. and WSW.
39.776	The ¼ sec. cor. of secs. 27 and 28, monumented with a stainless steel post, 2½ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 30 N., R. 56 E., executed under Group No. 648. Add the marks 1992 to the cap. From the cor. of secs. 27, 28, 33 and 34. N. 88°05' W., bet. secs. 28 and 33. Over gently rolling land, through scattered sagebrush, rabbitbrush and native grass.
4.90	Improved gravel road, on curve, from NW. to SSE.
9.50	Fence, parallels power line; enter meadow land.
10.50	Power line, bears N. 39½° W. and S. 39½° E.
20.165	Point for the E 1/16 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.