

328

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 36 N., R. 53 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 36 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Surveys Executed by  
A. Craven and J. E. Gignoux, U.S. Deputy Surveyors,  
in 1878,  
and H. B. Maxson, U.S. Deputy Surveyor,  
in 1896

The original corners were established for Tps. 36 and 37 N., but now these corners will refer to Tps. 36 and 36 $\frac{1}{2}$  N. only.

From the cor. of Tps. 36, 36 $\frac{1}{2}$  and 37 N., Rs. 53 and 54 E., monumented with a stainless steel post, 2 $\frac{1}{2}$  ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 37 N., R. 53 E., executed concurrently under this same Group.

N. 89° 27' W., bet. secs. 1 and 36.

Over rolling mountainous land, through scattered sagebrush, serviceberry, rabbitbrush and native grass.

40.07 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This point is used to control the N-S center line of sec. 36, T. 37 N., R. 53 E., to identify the position of the N $\frac{1}{2}$  of the NE $\frac{1}{4}$  of sec. 36, T. 37 N., R. 53 E., of the 1878 survey.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36 $\frac{1}{2}$ N R53E  
S 36  
 $\frac{1}{4}$  —  
S 1  
T36N  
1988

80.14 The cor. of secs. 1, 2, 35 and 36, monumented with a granite stone, 12X5X5 ins., plainly mkd. with 5 notches on W. edge and 1 notch on E. edge, firmly set 10 ins. in the ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T36 $\frac{1}{2}$ N R53E  
S 35 | S 36  
S 2 | S 1  
T36N  
1988