

348

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 37 N., R. 53 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T37N R53E <u>S 35   S 36</u> S 36 T36<sup>1</sup>/<sub>2</sub>N R53E</p> <p style="text-align: center;">1988</p> <p>Deposit the original cornerstone and reset the steel fence post, the 2 wooden posts and the PVC pipe alongside the stainless steel post.</p> <p>S. 89° 56' E., on the S. bdy. of sec. 36.</p> <p>Over rolling mountainous land, through scattered sagebrush, rabbitbrush and native grass.</p>
35.18	<p>The N <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 36, T. 36<sup>1</sup>/<sub>2</sub> N., R. 53 E., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 36<sup>1</sup>/<sub>2</sub> N., R. 53 E., executed concurrently under this same Group.</p>
39.94	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This lost corner will no longer function as a corner.</p> <p>Not monumented</p>
40.00	<p>Point for the S <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 36, established at 40.00 chs. in departure from the cor. of secs. 35 and 36, and on the S. bdy. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T37N R53E <u><sup>1</sup>/<sub>4</sub> S 36</u> T36<sup>1</sup>/<sub>2</sub>N R53E</p> <p style="text-align: center;">1988</p>
40.80	<p>Spur, projects SSE.</p>
71.90	<p>Ravine, drains NE.</p>
75.25	<p>Intersect the W. bdy. of sec. 31, T. 37 N., R. 54 E.</p> <p>Point for the closing cor. of Tps. 36<sup>1</sup>/<sub>2</sub> and 37 N., Rs. 53 E.</p>