

355

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 37 N., R. 53 E., MDM, NEVADA

CHAINS	Over rolling mountainous land.
4.20	Trail road, bears WNW. and ESE.
4.36	The N $\frac{1}{4}$ sec. cor. of sec. 32, T. 36 $\frac{1}{2}$ N., R. 53 E., monumented with a stainless steel post, 2 $\frac{1}{2}$ ins. diam., firmly set, showing 1 in. above ground, with a mound of stone S. of cor., with brass cap mkd. as described in the field notes of T. 36 $\frac{1}{2}$ N., R. 53 E., executed concurrently under this same Group.
4.60	Fence, bears WNW. and ESE.
7.20	Ravine drains WNW.
40.21	The cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 16X14X4 ins., dimly mkd. with 5 notches on E. edge and 1 notch on W. edge, firmly set 10 ins. in the ground, with a steel fence post set alongside. This cor. now refers to secs. 31 and 32 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T37N R53E <u>S 31 S 32</u> S 32 T36$\frac{1}{2}$N R53E </div>
	1988
	Deposit the original cornerstone and reset the steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the stainless steel post.
	<hr/>
	N. 89° 56' W., on the S. bdy. of sec. 31.
	Over rolling mountainous land, through scattered sagebrush, serviceberry, rabbitbrush and native grass.
4.20	The closing cor. of secs. 31 and 32, T. 36 $\frac{1}{2}$ N., R. 53 E., monumented with a stainless steel post, 2 $\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes T. 36 $\frac{1}{2}$ N., R. 53 E., executed concurrently under this same Group.
36.10	Ridge, bears N. and S.