

364

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 37 N., R. 53 E., MDM, NEVADA

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam.,
10 ins. in the ground to solid rock and in a mound of stone,
5 ft. base to top, with brass cap mkd.

T38N	R53E
S 31	S 32
S 6	S 5
T37N	

1988

Deposit the original cornerstone and reset the steel fence post,
5 $\frac{1}{2}$ ft. long, alongside the stainless steel post.

N. 89° 58' W., bet. secs. 6 and 31.

Over rolling mountainous land, through scattered sagebrush,
serviceberry, rabbitbrush and native grass.

39.83

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite
stone, 16X10X8 ins., plainly mkd. $\frac{1}{4}$ on N. face, firmly set
11 ins. in the ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam.,
24 ins. in the ground, with brass cap mkd.

T38N	R53E
S 31	
$\frac{1}{4}$	—
S 6	
T37N	

1988

Deposit the original cornerstone alongside the stainless steel
post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor.

N. 89° 38' W., beginning new measurement.

Over rolling mountainous land.