DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

	OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 53 E., MDM, NEVADA
CHAINS	
27.10	Ravine, drains SW.
30.50	Ravine, drains SE.
40.00	Ravine, drains NE.
40.11	The 1/4 sec. cor. of secs. 30 and 31, monumented with a granite stone, 12X8X4 ins., plainly mkd. 1/4 on N. face, firmly set 6 ins. in the ground, with a mound of stone N. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T37N R53E
	s 30
	s 31
	1988
·	Deposit the original cornerstone alongside the stainless steel post.
	N. 89° 56' W., beginning new measurement.
	Over rolling mountainous land.
31.20	Fence, bears NNW. and SSE.
31.25	Intersect the E. bdy. of sec. 36, T. 37 N., R. $52^{1}/_{2}$ E.
	The closing cor. of secs. 30 and 31, monumented with a granite stone, 13X8X6 ins., plainly mkd. with 5 notches on N. edge and 1 notch on S. edge and dimly mkd. "CC" on E. face, firmly set 9 ins. in the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 5 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T37N S 30 S 36 ————————————————————————————————————
	R52 ¹ / ₂ E S 31 R53E
	1988
	Deposit the original cornerstone alongside the stainless steel post.