DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

	OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 53 E., MDM, NEVADA
CHAINS	Over rolling mountainous land, through scattered sagebrush, rabbitbrush, serviceberry and native grass.
14.00	Saddle on ridge, bears E. and W.
28.80	Ridge, bears N. and S.
39.47	The $^{1}/_{4}$ sec. cor. of secs. 19 and 30, monumented with a granite stone, 14X10X7 ins., dimly mkd. $^{1}/_{4}$ on N. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T37N R53E
	1/ ₄
	s 30
	1988
	Deposit the original cornerstone alongside the stainless steel post.
	N. 89° 49' W., beginning new measurement. Over rolling mountainous land.
2.00	Seep spring, drains NW.
27.40	Fence, bears N. and S.
32.41	Intersect the E. bdy. of sec. 25, T. 37 N., R. $52^{1}/_{2}$ E.
	The closing cor. of secs. 19 and 30, monumented with a granite stone, 12X10X8 ins., plainly mkd. with 4 notches on N. edge, 2 notches on S. edge and "CC" on E. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T37N S 19 S 25 R52 1/2 E R53E
	1988
	Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, $2^1/_2$ ft. base, $1^1/_2$ ft. high, E. of cor.