DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 53 E., MDM, NEVADA

	T. 37 N., R. 53 E., MDM, NEVADA
CHAINS	N. 89° 55' W., bet. secs. 18 and 19.
	Over rolling mountainous land, through scattered sagebrush, rabbitbrush, serviceberry and native grass.
40.18	The $^1/_4$ sec. cor. of secs. 18 and 19, monumented with a conglomerate stone, 16X12X8 ins., plainly mkd. $^1/_4$ on N. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 20 ins. in the ground to solid rock and in a collar of stone, $1^{1}/_{2}$ ft. base to top, with brass cap mkd.
	T37N R53E
	1/ ₄
	s 19
	1988
	Deposit the original cornerstone alongside the stainless steel post.
:	S. 89° 52' W., beginning new measurement.
	Over rolling mountainous land.
21.70	Fence, bears N. and S.
31.01	Intersect the E. bdy. of sec. 24, T. 37 N., R. $52^{1}/_{2}$ E.
	The closing cor. of secs. 18 and 19, monumented with a granite stone, 14X10X8 ins., plainly mkd. with 3 grooves on N. face, 3 notches on S. edge and "CC" on E. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T37N S 18 S 24 —— CC R52 1/2 E S 19 R53E
	1988
	Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.