

DEPENDENT AND INDEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 53 E., MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>S. 89° 52' W., beginning new measurement.</p> <p>Over rolling mountainous land.</p> <p>39.64 The cor. of secs. 7, 8, 17 and 18.</p>
	<hr/> <p>S. 89° 13' W., bet. secs. 7 and 18.</p> <p>Over rolling mountainous land, through scattered sagebrush, rabbitbrush, serviceberry and native grass.</p> <p>9.00 Fence, bears N. and S.</p> <p>39.95 The 1/4 sec. cor. of secs. 7 and 18, monumented with a granite stone, 16X8X8 ins., plainly mkd. 1/4 on N. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R53E</p> <p>S 7</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S 18</p> <p>1988</p> </div>
	<p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>S. 89° 53' W., beginning new measurement.</p> <p>Over rolling mountainous land.</p> <p>30.49 Intersect the E. bdy. of sec. 13, T. 37 N., R. 52 1/2 E.</p> <p>The closing cor. of secs. 7 and 18, monumented with a basalt stone, 16X8X6 ins., plainly mkd. with 4 notches on S. edge, 2 notches on N. edge and "CC" on E. face, firmly set 7 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>