

414

DEPENDENT AND INDEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 53 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T37N R53E S 5 $\frac{1}{4}$ ——— S 8</p> <p style="text-align: center;">1988</p> <p>Deposit the original cornerstone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>S. 89° 49' W., beginning new measurement.</p> <p>Over rolling mountainous land.</p> <p>39.56 The cor. of secs. 5, 6, 7 and 8.</p>
	<hr/> <p>S. 89° 48' W., bet. secs. 6 and 7.</p> <p>Over rolling mountainous land, through scattered sagebrush, rabbitbrush, serviceberry and native grass.</p> <p>39.99 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a granite stone, 14X10X8 ins., plainly mkd. $\frac{1}{4}$ on N. face, firmly set 8 ins. in the ground, with a mound of stone N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T37N R53E S 6 $\frac{1}{4}$ ——— S 7</p> <p style="text-align: center;">1988</p>
	<p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>S. 89° 41' W., beginning new measurement.</p> <p>Over rolling mountainous land.</p> <p>1.40 Ravine, drains irregularly WSW.</p> <p>29.87 Intersect the E. bdy. of sec. 12, T. 37 N., R. 52$\frac{1}{2}$ E.</p> <p>The closing cor. of secs. 6 and 7, monumented with a basalt stone, 16X12X10 ins., plainly mkd. with 5 notches on S. edge, 1 notch on N. edge and "CC" on E. face, firmly set in a mound of stone.</p>