

425

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 37 N., R. 54 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 37 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
A. Craven and J. E. Gignoux, U.S. Deputy Surveyors,  
in 1878

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.,  
monumented with a granite stone, 19X9X8 ins., plainly mkd. with  
5 notches on E. edge and 1 notch on W. edge, firmly set in a mound  
of stone.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins.  
in the ground to solid rock and in a mound of stone, 3 ft. base to  
top, with brass cap mkd.

T37N R54E			
S	31		S 32
S	6		S 5
T36N			

1988

Deposit the original cornerstone alongside the stainless steel  
post.

N. 89° 46' W., bet. secs. 6 and 31.

Over rolling land, through scattered sagebrush, rabbitbrush and  
native grass.

- 7.49 Fence corner, bears N., 0.06 chs. dist., from which fences bear N.  
and W.
- 27.00 Trail road, bears NNW. and SSE.
- 27.70 Creek, 10 lks. wide, 4 ins. deep, in a wash, 30 lks. wide, 10 ft.  
deep, course SE.
- 40.12 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at proportionate  
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins.  
in the ground to solid rock and in a mound of stone, 2 $\frac{1}{2}$  ft. base  
to top, with brass cap mkd.

T37N R54E			
S	31		
$\frac{1}{4}$	_____		
S	6		
T36N			

1988