

426

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 54 E., MDM, NEVADA

CHAINS 80.57	<p>The cor. of Tps. 36, 36$\frac{1}{2}$ and 37 N., Rs. 53 and 54 E., monumented with a stainless steel post, 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 37 N., R. 53 E., executed concurrently under this same Group.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Surveys Executed by A. Craven and J. E. Gignoux, U.S. Deputy Surveyors, in 1878 and H. B. Maxson, U.S. Deputy Surveyor, in 1896</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp. N. 0° 06' E., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattered sagebrush, rabbitbrush and native grass.</p>
19.60	Trail road, bears ESE. and WNW.
40.57	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a granite stone, 13X9X4 ins., plainly mkd. $\frac{1}{4}$ on W. face, firmly set 8 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T37N R54E $\frac{1}{4}$ S 31 S 32</p> <p style="text-align: center;">1988</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <p>From this cor., the center of a detention pond berm, 3 chs. long, bears S. 8° E., 18.40 chs. dist.</p> <hr/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over rolling land.</p>
31.30	Ravine, drains ESE.