

448

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R65E <u>S 32   S 33</u> S 4 T39N R65E</p> <p style="text-align: center;">1989</p> <p>Deposit the original cornerstone and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 88° 18' W., on the S. bdy. of sec. 32.</p> <p>Over mountainous land, through scattered sagebrush, native grass and juniper.</p>
13.00	Trail road, bears N. and S.
21.60	Spur, slopes S.
40.41	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R65E <u><math>\frac{1}{4}</math> S 32</u> T39N R65E</p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p>
80.82	<p>Point for the cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R65E <u>S 31   S 32</u> S 5 T39N R65E</p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 88° 18' W., on the S. bdy. of sec. 31.</p> <p>Over mountainous land, through scattered sagebrush, native grass and heavy juniper.</p>