

454

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R64E R65E <math>\frac{1}{4}</math> S 12   S 7 1989</p> <p>Reset the original wooden post, the rebar and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0° 25' E., beginning new measurement.</p> <p>Over rolling land.</p>
32.80	Improved road, bears NNW. and SSE.
39.70	Trail road on curve, from NW. to NE.
40.02	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R64E R65E S 1   S 6 S 12   S 7 1989</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, a white PCV pipe, 6 ins. diam., firmly set in concrete and exposed 36 ins. above ground, bears N. 87° 18' W., 1.53 chs. dist.</p> <p>From this same corner, a rebar, ⅝ in. diam., with cap mkd. 1-6-7-12 RLS 6934, firmly set and exposed 6 ins. above ground, bears N. 86° 09' W., 1.53 chs. dist.</p> <p>The positions of these monuments are incorrect due to the recovery of original evidence at the ¼ sec. cor. of secs. 1 and 6, and are not utilized in the course of this survey.</p> <hr/> <p>N. 0° 25' E., bet. secs. 1 and 6.</p> <p>Over rolling land, through scattered sagebrush, native grass and juniper.</p>
25.00	Low saddle, bears NE. and SW.
40.02	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a redwood post, 3 ins. square, 36 ins. long, with illegible scribe marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p>