

455

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R64E R65E <math>\frac{1}{4}</math> S 1   S 6 1989</p> <p>Reset the original wooden post and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <p>This corner is located 30 lks. E. of an improved road; road bears N. and S.</p> <hr/> <p>N. 5° 53' W., beginning new measurement.</p> <p>Over rolling land.</p>
15.50	Improved road, bears NNE. and SSW.
40.66	Intersect the Eighth Standard Parallel North.
	<p>Point for the closing cor. of Tps. 40 N., Rs. 64 and 65 E., at proportionate distance; based on the closing distance referenced in the Fitzhugh survey under Contract No. 186; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R64E S 36 S 1   S 6 C   C R64E R65E T40N 1989</p> <p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <p>From this corner, the standard <math>\frac{1}{4}</math> sec. cor. of sec. 36, T. 41 N., R. 64 E., hereinbefore described, bears N. 88° 46' W., 9.99 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 40 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870</p> <hr/> <p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p>