

474

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R65E	
S 34	
S 3	S 2
T40N	R65E
C C	

1989

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the original closing cor. of secs. 2 and 3, monumented with a juniper post, 2 ins. square, 30 ins. long, with illegible scribe marks visible, loosely set in a mound of earth, bears N. 3° 16' E., 0.15 chs. dist. Add the marks AM and bury the post below the surface of the ground.

From this same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 41 N., R. 65 E., hereinbefore described, bears N. 88° 51' W., 9.98 chs. dist.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 2 is on the Eighth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R65E	
$\frac{1}{4}$ S 2	
T40N R65E	

1989

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the stainless steel post.

From this corner, the standard cor. of secs. 34 and 35, T. 41 N., R. 65 E., hereinbefore described, bears N. 88° 18' W., 9.87 chs. dist.

From the cor. of secs. 26, 34, 35 and Angle Point No. 8, Tract No. 42.

WEST, bet. secs. 27 and 34.