

480

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	N. 1° 21' E., beginning new measurement.
	Over rolling land.
25.70	Trail road, bears ENE. and WSW.
40.04	The cor. of secs. 9, 10, 15 and 16, (Hatch and Eaton survey), monumented with a juniper post, 3 ins. square, 30 ins. long, with illegible scribe marks visible, loosely set in a mound of earth. This cor. will now refer to the cor. of secs. 10, 15, 16 and Angle Point No. 4, Tract No. 39.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">AP 4 T40N TR 39   S 10 S 16   S 15 T40N R65E</p>
	1989
	Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.
	<hr/>
	From the cor. of secs. 10, 11, 14 and 15.
	N. 87° 42' W., bet. secs. 10 and 15.
	Over rolling land, through scattered sagebrush and native grass.
9.20	Improved road, parallels power line.
10.40	Power line, bears N. 46° W. and S. 46° E.
19.20	Fence, bears NNE. and SSW.
39.88	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T40N R65E S 10 ¼ ——— S 15</p>
	1989
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
52.80	Trail road, bears NW. and SE.
59.20	Trail road, bears NE. and SW.