CHAINS	
	Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.
	N. 0° 53′ E., beginning new measurement.
	Over rolling land.
22.10	Bladed road, bears ENE. and WSW.
39.96	The original closing cor. of secs. 3 and 4, monumented with a juniper post, 3 ins. square, 30 ins. long, with illegible scribe marks visible, loosely set in a mound of earth. Add the marks AM and bury the wooden post below the surface of the ground.
40.02	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R65E
S 33
S 4 | S 3
T40N | R65E
C C

1989

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, the standard ¼ sec. cor. of sec. 33, T. 41 N., R. 65 E., hereinbefore described, bears N. 88° 42′ W., 11.50 chs. dist.

From the cor. of secs. 22, 28, Angle Point No. 6, Tract No. 41 and Angle Point No. 3, Tract No. 42.

WEST, bet. secs. 21 and 28.

Over rolling land, through scattered sagebrush, native grass and medium juniper.

40.00 Point for the ¼ sec. cor. of secs. 21 and 28, established at record bearing and distance from the Hatch and Eaton cor. of secs. 21, 22, 27 and 28; there is no remaining evidence of the original corner. This cor. will now refer to the ¼ sec. cor. of sec. 28 and Angle Point No. 5, Tract No. 41.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.