

487

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS

T40N	
S 4	TR 38
CC ———	
S 8	
R65E	

1989

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, the ¼ sec. cor. of secs. 4 and 9, (Hatch and Eaton survey), hereinbefore described, bears S. 88° 12' E., 34.697 chs. dist.

From this same corner, the cor. of secs. 4, 5, 8 and 9, (Fitzhugh survey), hereinafter described, bears N. 0° 56' E., 1.44 chs. dist.

Point for the S ¼ sec. cor. of sec. 4, identical with Angle Point No. 2, Tract No. 38, established on the N. bdy. of sec. 9, (Fitzhugh survey), and on the N-S center line of sec. 4, (Hatch and Eaton survey).

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R65E
¼ S 4
AP 2
TR 38

1989

Set a steel fence post, 5½ ft. long, alongside the stainless steel post.

From this corner, the N ¼ sec. cor. of sec. 4, hereinafter described, bears N. 0° 43' E.

From this same corner, the ¼ sec. cor. of secs. 4 and 9, (Hatch and Eaton survey), hereinbefore described, bears S. 0° 43' W.

From this same corner, the ¼ sec. cor. of secs. 4 and 9, (Fitzhugh survey), hereinafter described, bears S. 89° 43' E., 5.610 chs. dist.

From this same corner, the cor. of secs. 4, 5, 8 and 9, (Fitzhugh survey), hereinafter described, bears N. 89° 43' W., 34.690 chs. dist.

From the cor. of secs. 4 and 5.

N. 0° 21' E., bet. secs. 4 and 5.