

489

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R65E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 4 T40N R65E </p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.</p> <p>From this corner, the standard cor. of secs. 32 and 33, T. 41 N., R. 65 E., hereinbefore described, bears N. 88° 23' W., 10.49 chs. dist.</p> <hr/> <p>From the cor. of secs. 4 and 5.</p> <p>N. 89° 08' W., on the S. bdy. of sec. 5.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
31.855	The N ¹ / ₄ sec. cor. of sec. 8, hereinafter described.
40.705	<p>Point for the ¹/₄ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the S ¹/₄ sec. cor. of sec. 5.</p> <p>No permanent monument established.</p>
41.00	Enter scattered juniper.
69.73	The closing cor. of secs. 6 and 8, hereinafter described.
81.41	<p>The cor. of secs. 5, 6, 7 and 8, (Hatch and Eaton survey), monumented with a mound of stone. No marked stone found. This mound of stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner. This cor. will now refer to the SW. cor. of sec. 5 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T40N R65E S 5 S 6 </p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, NE. of cor.</p> <hr/> <p>N. 0° 23' E., bet. secs. 5 and 6.</p>