

492

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, a rebar, ⅝ in. diam., firmly set and exposed 6 ins. above ground, with a steel fence post alongside, bears S. 21° 21' E., 5.22 chs. dist.</p>
	<hr/> <p>S. 88° 39' E., bet. secs. 27 and 34.</p>
	<p>Over rolling land, through scattered sagebrush and native grass.</p>
5.00	<p>Low ridge, N. and S.</p>
35.324	<p>Intersect line 6-7, Tract No. 42, hereinafter described, from which Angle Point No. 7, Tract No. 42, bears S. 0° 26' W., 4.919 chs. dist.</p>
39.50	<p>Point for the ¼ sec. cor. of secs. 27 and 34, established at record bearing and distance from the Fitzhugh cor. of secs. 27, 28, 33 and 34; there is no remaining evidence of the original corner. This cor. will now refer to Angle Point No. 4, Tract No. 43.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">TR 42 AP 4 TR 43 TR 42</p> <p style="text-align: center;">1989</p>
	<p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, a rebar, ⅝ in. diam., firmly set and exposed 6 ins. above ground, with a steel fence post lying alongside, bears S. 32° 46' E., 5.75 chs. dist.</p>
	<hr/> <p>From the cor. of secs. 28, 33, 34 and Angle Point No. 3, Tract No. 43.</p> <p>N. 1° 00' E., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
16.923	<p>Intersect line 5-6, Tract No. 42, hereinafter described, from which Angle Point No. 5, Tract No. 42, bears N. 86° 47' W., 5.975 chs. dist.</p>
20.04	<p>Point for the S ⅓ sec. cor. of secs. 27 and 28. This cor. will now refer to Angle Point No. 2, Tract No. 43.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>