

495

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">           T40N AP 4  <u>S 20   TR 40</u>            S 29   S 28            R65E         </p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
	<p style="text-align: center;">S. 89° 22' E., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattered sagebrush, native grass and heavy juniper.</p>
13.364	<p>Intersect line 3-4, Tract No. 41, hereinafter described, from which Angle Point No. 4, Tract No. 41, bears S. 1° 30' W., 3.248 chs. dist.</p>
19.858	<p>Point for the W ¼ sec. cor. of secs. 21 and 28. This cor. will now refer to Angle Point No. 5, Tract No. 40.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">           AP 5            TR 40    <u>TR 41</u>            TR 41         </p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, the cor. of secs. 21, 22, 27 and 28, (Fitzhugh survey), monumented with a redwood post, 3 ins. square, 36 ins. long, with illegible scribe marks visible, firmly set and exposed 30 ins. above ground, bears S. 89° 22' E., 59.572 chs. dist. Add the marks AM and bury the post below the surface of the ground.</p>
	<p>From the cor. of secs. 20, 28, 29 and Angle Point No. 4, Tract No. 40.</p> <p>N. 0° 53' E., bet. secs. 20 and 21.</p> <p>Over mountainous land, through scattered sagebrush, native grass and juniper.</p>