

511

SURVEY OF TRACT NO. 37,
TOWNSHIP 40 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS

Tract No. 37, identical with the SW¹/₄ of the NE¹/₄ of sec. 6, as shown on plat approved November 9, 1870.

This tract was located by the subdivision of sec. 6 as surveyed by U.S. Deputy Surveyors A. J. Hatch and J. H. Eaton, in the usual manner. The field notes of the boundaries of Tract No. 37 only are furnished herewith.

Point for Angle Point No. 1, Tract No. 37, identical with the NE ¹/₁₆ sec. cor. of sec. 6, as surveyed by U.S. Deputy Surveyors A. J. Hatch and J. H. Eaton.

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R65E
S 6
AP 1 |
TR 37 |

1989

Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.

From this corner, an iron pipe, 2 ins. diam., at southerly end of water trough, (Indian Springs) bears S. 71° 19' W., 2.40 chs. dist.

N. 88° 56' W., on line 1-2, Tract No. 37.

19.71

Point for Angle Point No. 2, Tract No. 37, identical with the C-N ¹/₁₆ sec. cor. of sec. 6, as surveyed by U.S. Deputy Surveyors A. J. Hatch and J. H. Eaton.

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.

T40N R65E
S 6
AP 2 |
TR 37 |

1989

Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.

S. 1° 46' E., on line 2-3, Tract No. 37.