

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 16 N., R. 33 E., MDM, NEVADA

CHAINS									
	Set a steel fence post, 5 <sup>1</sup> / <sub>2</sub> ft. long, alongside the stainless steel post.								
40.020	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set and exposed 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 16 N., R. 33 E., executed under Group No. 155. Add the marks T16NR33E 1991 to the brass cap.</p> <p>From this corner, U.S.G.S. triangulation station "BENCH MARK X 46", monumented with a standard brass tablet set in a concrete block, 6 ins. squared, exposed 3 ins. above the surface of the ground, with brass tablet mkd. X 46 1934, bears N. 59°48.9' W., 34.992 chs. dist.</p> <hr/> <p>S. 89°53.2' W., beginning new measurement.</p> <p>Over rolling land.</p>								
20.020	<p>Point for the W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td style="text-align: center;">S 5</td> </tr> <tr> <td style="text-align: center;">W <sup>1</sup>/<sub>16</sub></td> <td style="text-align: center;">-----</td> </tr> <tr> <td></td> <td style="text-align: center;">S 8</td> </tr> <tr> <td></td> <td style="text-align: center;">1991</td> </tr> </table> </div> <p>Set a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, alongside the stainless steel post.</p>		S 5	W <sup>1</sup> / <sub>16</sub>	-----		S 8		1991
	S 5								
W <sup>1</sup> / <sub>16</sub>	-----								
	S 8								
	1991								
25.90	State Route 31, on curve, from SSW. to NNW.								
40.040	The cor. of secs. 5, 6, 7 and 8.								
<hr/> <p>SUBDIVISION OF SECTION 2, T. 16 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>									
20.001	<p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 11.</p> <p>N. 0°02.0' E., on the N-S center line of sec. 2.</p> <p>Over level land, across dry lake bed.</p> <p>Point for the C-S <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p>								