

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
TOWNSHIP 41 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870</p> <hr/> <p>From the standard cor. of Tps. 41 N., Rs. 65 and 66 E., monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set and exposed 4 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 40 N., R. 66 E., executed under Group No. 582.</p> <p>N. 0°09' E., bet. secs. 31 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
9.60	Improved road, bears ENE. and WSW.
40.89	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R65E R66E <sup>1</sup>/<sub>4</sub> S 36   S 31</p> <p style="text-align: center;">1989</p> <p>Set a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, alongside the stainless steel post.</p>
79.00	Fence, bears E. and W.
81.78	<p>The cor. of secs. 25, 30, 31 and 36, monumented with the decayed remains of a juniper post, with illegible scribe marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R65E R66E <u>S 25   S 30</u> S 36   S 31</p> <p style="text-align: center;">1989</p> <p>Reset the original wooden post and set a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 1°38' E., bet. secs. 25 and 30.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>