

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 41 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 41 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870, and the Resurvey Executed by Compassman H. Thurtell in 1904
	From the standard cor. of Tps. 41 N., Rs. 64 and 65 E., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 40 N., R. 65 E., executed under Group No. 673.
	N. 1°55' E., bet. secs. 31 and 36.
	Over rolling land, through scattered sagebrush and native grass.
40.32	The $^{1}/_{4}$ sec. cor. of secs. 31 and 36, monumented with the decayed remains of a juniper post, 1 in. square, 6 ins. long, with illegible scribe marks visible, loosely set in a mound of earth.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R64E_R65E
	s 36 s 31
	1989
	Reset the original wooden post and set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
	N. 0°05' W., beginning new measurement.
	Over rolling land.
19.10	Power line, bears N. $35^{1}/_{2}^{\circ}$ W. and S. $35^{1}/_{2}^{\circ}$ E.
20.10	Improved gravel road, parallels power line.
36.50	Telephone cable, underground, bears WNW. and ESE.
40.23	The cor. of secs. 25, 30, 31 and 36, monumented with a juniper post, 2 ins. square, 20 ins. long, with illegible scribe marks visible, loosely set in a mound of earth.
:	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R64E R65E <u>S 25 S 30</u> S 36 S 31
	1989