

117

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 41 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS													
	<div data-bbox="903 282 1050 444"> <table> <tr><td>T41N</td><td></td></tr> <tr><td>R64E</td><td>T41N</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td></td><td>S 6</td></tr> <tr><td>S 12</td><td>R65E</td></tr> </table> </div> <div data-bbox="945 472 1008 495">1989</div> <div data-bbox="445 526 1473 584">Deposit the original cornerstone and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</div> <div data-bbox="445 661 1068 689">N. 1°57' E., beginning new measurement.</div>	T41N		R64E	T41N	S 1		<hr/>			S 6	S 12	R65E
T41N													
R64E	T41N												
S 1													
<hr/>													
	S 6												
S 12	R65E												
33.35	<div data-bbox="445 713 1473 804">The <math>\frac{1}{4}</math> sec. cor. of sec. 6, monumented with a limestone, 15X12X8 ins., mkd. <math>\frac{1}{4}</math> on E. face, firmly set and exposed 6 ins. above ground.</div> <div data-bbox="445 830 750 858">At the corner point</div> <div data-bbox="445 879 1473 940">Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div data-bbox="895 968 1041 1078"> <table> <tr><td>T41N</td><td></td></tr> <tr><td>R64E</td><td>R65E</td></tr> <tr><td></td><td><math>\frac{1}{4}</math></td></tr> <tr><td>S</td><td>6</td></tr> </table> </div> <div data-bbox="929 1103 991 1127">1989</div> <div data-bbox="445 1153 1473 1213">Deposit the marked stone and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</div> <div data-bbox="445 1293 1068 1321">N. 1°56' E., beginning new measurement.</div>	T41N		R64E	R65E		$\frac{1}{4}$	S	6				
T41N													
R64E	R65E												
	$\frac{1}{4}$												
S	6												
6.58	<div data-bbox="445 1347 1473 1438">The <math>\frac{1}{4}</math> sec. cor. of sec. 1, T. 41 N., R. 64 E., monumented with a limestone, 12x12x8 ins., mkd. <math>\frac{1}{4}</math> on W. face, firmly set and exposed 6 ins. above ground.</div> <div data-bbox="445 1463 750 1491">At the corner point</div> <div data-bbox="445 1513 1473 1573">Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div data-bbox="887 1599 1033 1709"> <table> <tr><td>T41N</td><td></td></tr> <tr><td>R64E</td><td>R65E</td></tr> <tr><td><math>\frac{1}{4}</math></td><td></td></tr> <tr><td>S 1</td><td></td></tr> </table> </div> <div data-bbox="929 1735 991 1759">1989</div> <div data-bbox="445 1785 1473 1845">Deposit the original cornerstone and set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</div> <div data-bbox="445 1901 1068 1929">N. 1°56' E., beginning new measurement.</div>	T41N		R64E	R65E	$\frac{1}{4}$		S 1					
T41N													
R64E	R65E												
$\frac{1}{4}$													
S 1													