

168

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 42 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870</p> <hr/> <p>From the cor. of Tps. 41 and 42 N., Rs. 65 and 66 E., monumented with a stainless steel post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 41 N., R. 65 E., executed under Group No. 676.</p> <p>N. 0°30' E., bet. secs. 31 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>40.10 The ¼ sec. cor. of secs. 31 and 36, monumented with the decayed remains of a juniper post, 1 in. square, 18 ins. long, with illegible scribe marks visible, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R65E R66E 1/4 S 36 S 31</p> <p>1989</p> </div> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°34' E., beginning new measurement.</p> <p>Over rolling land.</p>
36.90	Fence, bears NE. and SW.; enter nearly level meadow land.
39.95	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R65E R66E S 25 S 30 S 36 S 31</p> <p>1989</p> </div> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <hr/>