

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 42 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 41 N., R. 65 E., executed under Group No. 676.</p>
	<p>N. 0°42' E., bet. secs. 35 and 36.</p>
	<p>Over nearly level meadow land.</p>
40.41	<p>Point for the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R65E           <sup>1</sup>/<sub>4</sub> S 35   S 36  1989</p>
	<p>Set a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, alongside the stainless steel post.</p>
61.50	<p>Thousand Springs Creek, 20 lks. wide, 2 ft. deep, course E.</p>
74.10	<p>Fence, bears NE. and SW.; enter rolling land, through scattered sagebrush, greasewood and native grass.</p>
74.50	<p>Improved gravel road, bears NE. and SW.</p>
80.82	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a juniper post, 2 ins. square, 20 ins. long, with illegible scribe marks visible, loosely set in a mound of earth.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T42N R65E S 26   S 25 S 35   S 36  1989</p>
	<p>Reset the original wooden post and set a steel fence post, 5<sup>1</sup>/<sub>2</sub> ft. long, alongside the stainless steel post.</p>
	<p>From this corner, U.S.C. &amp; G.S. Bench Mark, monumented with a standard brass tablet, firmly set in a concrete cylinder, 8 ins. diam., exposed 6 ins. above ground, with brass tablet mkd. L 192 1958, bears N. 66°10' E., 19.99 chs. dist.</p> <hr/>