DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 20 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by
U. S. Deputy Surveyors R. H. Woods and W. H. Myrick,
in 1881-82

From the cor. of Tps. 20 S., Rs. 62 and 63 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62. E., executed under Group No. 708. Add the marks 1992 to the brass cap.

From this point U.S.C. & G.S. triangulation station "SUNRISE", monumented with a standard brass tablet, $3^{1}/_{2}$ ins. diam., firmly cemented in limestone, mkd. SUNRISE 1947, bears N. 14°54.5′ W. (mean bearing), 113.727 chs. dist.

N. 0°10.1' E., on the E. bdy. of sec. 36.

Over gently rolling land, covered with scattered creosote brush and cacti.

40.336

The $^{1}/_{4}$ sec. cor. of secs. 31 and 36, monumented with a sandstone, 7 x 10 x 21 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. $^{1}/_{4}$ on W. face. This cor. will now function as the $^{1}/_{4}$ sec. cor. of sec. 36, T. 20 S., R. 62 E., only.

At the corner point

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 12 ins. in the ground to bedrock over a DEEP-1 magnetic marker, and in a mound of stone 4 ft. base to top with brass cap mkd.

T20S R62E R63E

1992

Deposit the original cornerstone alongside the stainless steel post.

From this corner, a rebar $^5/_8$ in. diam., with metal tag mkd. ARIZ RLS 4171, firmly set, projecting 4 ins. above the ground, with iron cap mkd. $^1/_4$ S31 S36, bears S. 54°17.8′ W., 0.491 chs. dist.

N. 0°10.8' E., beginning new measurement.

Over rolling land.

40.188

The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 10 X 11 X 25 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 5 notches on the N. face and 1 notch on the S. face. This cor. will now function as the cor. of secs. 25 and 36, T. 20 S., R. 62 E., only.

At the corner point