DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 62 EAST. MOUNT DIABLO MERIDIAN. NEVADA

	THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of the Survey Executed by U. S. Deputy Surveyors M. Brunt and W. H. Proctor in 1881, and the Dependent Resurvey by Associate Cadastral Engineer Emil Voigt and Assistant Cadastral Engineer J. W. Hardison in 1943.
	From the standard cor. of Tps. 20 S., Rs. 62 and 63 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel South, through Ranges 63, 64, and 65 E., executed under Group No. 169. Add the marks 1991 to the brass cap.
	From this corner, U.S.C.&G.S. triangulation station "SUNRISE", monumented with a standard brass tablet, 3 1/2 ins. diam., firmly cemented in limestone, mkd. SUNRISE 1947, bears N. 14°54.5′ W., 113.727 chs. dist.
	S. 89°45.3' W., on the S. bdy. of sec. 36.
	Over mountainous land, through scattered creosote brush, asc. over steep broken E. slope.
14.481	The closing cor. of Tps. 21 S., Rs. 62 and 63 E., hereinafter described.
28.40	Broken ledgy spur, slopes S.; desc. over W. slope.
36.90	Broken ledgy spur, slopes S.
37.567	The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 336. Add the marks T20S R62E 1991 to the brass cap.
	S. 87°40.1' W., beginning new measurement.
	Over mountainous land; asc. over broken ledgy E. slope.
6.30	Broken ledgy spur, slopes S.; desc. over ledgy W. slope.
13.935	The witness cor. to the N $^{1}/_{4}$ sec. cor. of sec. 1, T. 21 S., R. 62 E., hereinafter described.
13.969	The true point for the N $^1/_4$ sec. cor. of sec. 1, T. 21 S., R. 62 E., hereinafter described.
38.061	The standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 336. Add the marks 1991 to the brass cap.