

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 41<sup>1</sup>/<sub>2</sub> NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
78.27	The closing cor. of secs. 1 and 2, T. 41 N., R. 25 E., bears NORTH, 0.9 lks. dist., hereinafter described.										
80.00	Point for the cor. of secs. 35 and 36, NORTH, 0.9 lks. from the tangent.  Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T41<sup>1</sup>/<sub>2</sub>N R25E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">T41N</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table> </div> Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush and bunchgrass.	T41 <sup>1</sup> / <sub>2</sub> N R25E		S 35	S 36	S 2		T41N		1988	
T41 <sup>1</sup> / <sub>2</sub> N R25E											
S 35	S 36										
S 2											
T41N											
1988											
<hr/> <p>SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, TOWNSHIP 41 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>											
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set and exposed 14 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 41 N., R. 26 E., executed under Group No. 3.  WEST, on the S. bdy. of sec. 13, on a transit line describing the tangent.  Over rolling land, through scattered undergrowth.										
14.00	Ravine, drains SW.										
40.00	Point for the <sup>1</sup> / <sub>4</sub> sec. cor. of sec. 13, NORTH, 0.2 lks. from the tangent.  Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.  <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T41N R25E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"><sup>1</sup>/<sub>4</sub> S 13</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">1988</td> </tr> </table> </div>	T41N R25E		<sup>1</sup> / <sub>4</sub> S 13		1988					
T41N R25E											
<sup>1</sup> / <sub>4</sub> S 13											
1988											
80.00	Point for the cor. of secs. 13 and 14, NORTH, 0.9 lks. from the tangent.  Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.										