SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 411/2 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set and in a mound of stone, 3 ft. base to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 41 N., R. 25 E., executed concurrently under this same Group.

NORTH, bet. secs. 35 and 36.

Over rolling land, through scattered undergrowth.

40.87

Intersect the S. bdy. of sec. 36, T. 42 N., R. 25 E.

Point for the closing cor. of secs. 35 and 36, T. $41^{1}/_{2}$ N., R. 25 E.

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

1988

From this corner, the cor. of secs. 35 and 36, T. 42 N., R. 25 E., monumented with a stainless steel post, $2^1/_2$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 42 N., R. 25 E., executed concurrently under this same Group, bears S. 89°55′ W., 3.38 chs. dist.

Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush and bunchgrass.

The point for the $^{1}/_{4}$ sec. cor. of sec. 36 only, is on the S. bdy. of T. 42 N., R. 25 E., and at 40.00 chs. in departure from the closing cor. of secs. 35 and 36.

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 36 T41¹/₂N R25E

1988

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the $^{1}/_{4}$ sec. cor. of sec. 36, T. 42 N., R. 25 E., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 42 N., R. 25 E., executed concurrently under this same Group, bears S. 89°55′ W., 1.84 chs. dist.