

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by G. W. Garside, U.S. Deputy Surveyor, in 1873</p> <hr/>
	<p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°07' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
41.54	<p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a basalt stone, 10X8X6 ins., plainly mkd. $\frac{1}{4}$ on top face, firmly set in a mound of stone. (Record charred post.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R25E S 35 $\frac{1}{4}$ S 36 1988</p> <p>Deposit the original cornerstone and set a steel fence post, 5$\frac{1}{2}$ ft. long, alongside the stainless steel post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 0°16' W., beginning new measurement.</p> <p>Over rolling land.</p>
35.40	Trail road, bears NE. and SW.
40.80	Fence, bears E. and W.
42.05	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a basalt stone, 12X10X10 ins., plainly mkd. on top face with 1 groove near the south side and 6 grooves near the east side, firmly set in a mound of stone. (Record charred post.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R25E S 26 S 25 S 35 S 36 1988</p>