

SUBDIVISION OF SECTION 35,
TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} E \frac{1}{16} \\ C \frac{\quad}{\quad} C \\ S \ 35 \end{array}$ <p style="text-align: center;">1988</p>
28.00	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Tollhouse Canyon, drains SSE.</p>
41.16	<p>The center ¹/₄ sec. cor. of sec. 35.</p>
61.71	<p>Point for the C-W 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> $\begin{array}{c} W \frac{1}{16} \\ C \frac{\quad}{\quad} C \\ S \ 35 \end{array}$ <p style="text-align: center;">1988</p>
82.26	<p>The ¹/₄ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set and exposed 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 42 N., R. 25 E., executed under Group No. 342. Remark the brass cap to read as follows:</p> $\begin{array}{c} T42N \ R25E \\ \quad \frac{1}{4} \\ \quad S \ 35 \end{array}$ <p style="text-align: center;">1988 1946</p> <hr/> <p style="text-align: center;">SURVEY OF THE 1988-1991 MEANDER LINES AND AN INFORMATIVE TRAVERSE OF THE 1988-1991 BANK OF A PORTION OF SUMMIT LAKE, TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1988-1991 meander cor. of secs. 31 and 36, on the southwest bank of Summit Lake, hereinbefore described.</p> <p>With the 1988-1991 meanders of Summit Lake in sec. 36.</p> <p>N. 49°29' W., 8.36 chs.</p> <p>N. 28°30' W., 8.53 chs.</p> <p>N. 2°26' E., 0.13 chs. Intersect the computed E-W center line of the SE¹/₄ of sec. 36.</p>