DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 1 S., R. 35 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Reestablishment of the Survey Executed by D. H. Barker, A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1877
	Beginning at the cor. of secs. 15, 16, 21 and 22, monumented with a red granite stone, 14x6x5 ins., plainly mkd. with 3 grooves on the S. and E. faces, loosely set 2 ins. in the ground, with a railroad tie, 5x7 ins. square, firmly set projecting 62 ins., 0.8 ft. northwesterly.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnet, with brass cap mkd.
	T1S R35E S 16 | S 15 S 21 | S 22
	1993
	Deposit the original cornerstone alongside the stainless steel post.
	From this corner, angle point in single wooden pole power line, bears northwesterly 2.5 ft. dist., from which power line bears N. and W.
	N. 0°25'30" E., bet. secs. 15 and 16.
	Over nearly level sandy land, through scattered sagebrush and native grass, along easterly side of power line.
17.20	Trail road, bears E. and W.
21.58	Angle point in single wooden pole power line, bears WEST, 0.5 ft. dist., from which power line bears S. and W.
43.196	The $^1/_4$ sec. cor. of secs. 15 and 16, monumented with a volcanic stone, 10x8x8 ins., plainly mkd. $^1/_4$, lying next to a rebar, $^5/_8$ in. diam., 25 ins. long, firmly set 17 ins. in the ground, with copper tag, mkd. PLS 4248 and railroad tie, 5x7 ins. square, firmly set projecting 62 ins., 0.5 ft. easterly.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnet, with brass cap mkd.
	T1S R35E $^1/_4$ S 16 | S 15
	1993 Deposit the original cornerstone and reset the rebar, alongside the stainless steel post.
	N. 0°26'40" E., beginning new measurement.