

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey
Executed by G. W. Ridgway, Cadastral Engineer,
in 1930-31

From the standard cor. of secs. 32 and 33, T. 16 N., R. 33 E., monumented with an iron post, 2 ins. diam., firmly set showing 8 ins. above ground, with brass cap mkd. as described in the field notes of T. 15 N., R. 33 E., executed concurrently under this same Group.

N. 0°02.6' W., bet. secs. 32 and 33.

Over nearly level land, covered with native grass and sagebrush.

20.006 Point for the S $\frac{1}{16}$ sec. cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

S $\frac{1}{16}$
S 32 | S 33

1991

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the stainless steel post.

40.012 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set showing 10 ins. above ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 33 E., executed under Group No. 155.

Remark the brass cap to read:

T16N R33E

S 32 | $\frac{1}{4}$ S 33

1991

1931

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the iron post.

SUBDIVISION OF SECTION 32,
T. 16 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

From the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 16 N., R. 33 E., monumented with an iron post, 1 in. diam., firmly set showing 10 ins. above ground, with brass cap mkd. as described in the field notes of T. 15 N., R. 33 E., executed concurrently under this same Group.

N. 0°01.8' W., on the N-S center line of sec. 32.

Over nearly level land, covered with native grass and sagebrush.