DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by R. H. Woods and W. H. Myrick in 1881

Beginning at the cor. of secs. 7, 8, 17 and 18, monumented with a mound of earth and stone, 5 ft. diam.; a limestone, 18x12x6 ins., mkd. with 4 grooves on one face, was found lying loosely on the ground a short distance downslope.

At the corner point at the center of the mound

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

1994

Deposit mkd. stone alongside the stainless steel post.

From this cor. National Geodetic Survey station "KIM", monumented with a standard U.S. Coast and Geodetic Survey brass tablet, set in concrete, mkd. KIM 1957, bears S. 71°33′00" E., 144.852 chs. dist.

S. 89°44'20" W., bet. secs. 7 and 18.

40.228

Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

1994

Corner is located in the W bank of a wash which drains S.

64.90

Underground gas pipeline, bears NE and SW.

69.55

Railroad track, bears N and S.

80.626

The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the W. bdy. executed by S. R. Lambeth in 1987-89, and a mound of stone W of the corner.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°06'20" W., bet. secs. 7 and 8.