DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	in Record of Survey File 039, Page 092, in the office of the Clark County Recorder; this is accepted as a careful and faithful determination of the corner position.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.
	$W 1/16 \frac{s 6}{s 7}$
	1994
	Deposit the rebar inside the stainless steel post.
	S. 88°30'00" W., beginning new measurement.
20.178	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the W. bdy. executed by S. R. Lambeth in 1987-89, and a mound of stone W of the corner.
	SUBDIVISION OF SECTION 7, T. 15 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°16'20" W., on the N-S center line of sec. 7.
17.30	Underground gas pipeline, bears NE and SW.
18.60	Power transmission line, bears NE and SW.
21.95	Power transmission line, bears NE and SW.
24.00	Power transmission line, bears NE and SW.
40.658	Point for the center $1/4$ sec. cor. of sec. 7, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.
	T15S R66E C 1/4 S 7
	1994
61.491	Point for the C-N 1/16 sec. cor. of sec. 7.
	Set an aluminum tablet, 3 ins. diam., in concrete, inside a PVC pipe, projecting 6 ins. above the ground, and over a rebar, 12 ins. long, $\frac{5}{8}$ ins. diam., drilled 6 ins. in solid bedrock, mkd.