DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 19 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 19 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyors J. M. Brunt and W. H. Proctor, in 1881
	From the cor. of secs. 3, 4, 33 and 34, monumented with an iron post, $2^{1}/_{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 18 S., R. 59 E., executed under Group No. 612.
	S. 89°58.5' W., bet. secs. 4 and 33.
	Over rolling land, covered with medium yuccas, cacti, creosote brush and scattered mesquite and joshua trees.
40.692	The $^{1}/_{4}$ sec. cor. of secs. 4 and 33, monumented with a conglomerate stone, 14x8x6 ins., mkd. $^{1}/_{4}$ on the N. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T18S R59E
	1/4 S 33
	S 4 T19S
	1991
	Deposit the original cornerstone alongside the stainless steel post.
	S. 89°26.5' W., beginning new measurement.
	Over rolling land.
40.778	The cor. of secs. 4, 5, 32 and 33, monumented with an unmarked sandstone, 14x8x8 ins., firmly set in a mound of stone. This unmarked stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T18S R59E S 32 S 33
	S 5 S 4 T19S
	1991